

CABLES

NUMBER	SIDE VIEW	DESCRIPTION	RANGE °C	RANGE °F	DIAMETER in.	pF/ft.
J1		Coaxial, low noise, orange, PVC jacket	–55 to 80	–67 to 176	0.088	30
J3		Coaxial, low noise, high temperature, red, Teflon® jacket	–100 to 260	–148 to 500	0.085	30
J4		Coaxial, RG 174, black, PVC jacket	–55 to 80	–67 to 176	0.105	30
J5A		Coaxial, RG 58, black, PVC jacket	–40 to 105	–40 to 221	0.190	30
J6		Coaxial, underwater, black, Polyurethane jacket	–20 to 90	–4 to 194	0.156	44
J8		Twisted pair, shielded, underwater, black Polyurethane jacket	–20 to 90	–4 to 194	0.156	23
J9		Twisted pair, shielded, gray, PVC jacket	–55 to 80	–67 to 176	0.230	32
J9A		Twisted pair, shielded, brown, PVC jacket	–55 to 105	–67 to 221	0.200	28
J9B		Three conductor, shielded, gray, PVC jacket	–55 to 80	–67 to 176	0.240	44
J9T		Coaxial, RG 59, black, Teflon® jacket	–80 to 150	–112 to 302	0.190	20
J9T2		Twisted pair, shielded, white Tefzel® jacket	–80 to 150	–112 to 302	0.190	27
J9T2A		Twisted pair, shielded, yellow Teflon® jacket	–80 to 200	–112 to 392	0.190	27

CABLES

NUMBER	SIDE VIEW	DESCRIPTION	RANGE °C	RANGE °F	DIAMETER in.	pF/ft.
J9T2AS		Twisted pair, shielded, yellow Teflon® jacket with stainless steel braid	–80 to 200	–112 to 392	0.210	27
J9T2S		Twisted pair, shielded, white Tefzel® jacket, with stainless steel braid	–80 to 150	–112 to 302	0.210	27
J9T3		Three conductor, shielded, white Tefzel® jacket	–80 to 150	–112 to 302	0.190	27
J9T3A		Three conductor, shielded, yellow Teflon® jacket	–80 to 200	–112 to 392	0.190	27
J9T3S		Three conductor, shielded, white Tefzel® jacket, with stainless steel braid	–80 to 150	–112 to 302	0.210	27
J9T4		Four conductor, shielded, red Teflon® jacket	–80 to 200	–112 to 392	0.190	30
J9T4A		Four conductor, shielded, yellow Teflon® jacket	–80 to 200	–112 to 392	0.190	27
J10		Twisted pair, shielded, gray Enviroprene™ jacket	–50 to 125	–58 to 257	0.190	30
J41		Coaxial, black, PVC jacket, *for SNAP™ sensors*	–55 to 60	–67 to 140	0.097	18
J51		Coaxial, retractable, black, Neoprene jacket, available in 4 and 12 ft. extended length	–55 to 90	–67 to 194	0.170	30
J52		Twisted pair, shielded, polyurethane jacket, available in 4 ft. extended length	–20 to 80	–4 to 176	0.156	39
J61		Coaxial, underwater, black, Polyurethane jacket	–20 to 90	–4 to 194	0.190	44
J81		Twisted pair, shielded, underwater, black, Polyurethane jacket	–20 to 90	–4 to 194	0.190	28

CABLES

NUMBER	SIDE VIEW	DESCRIPTION	RANGE °C	RANGE °F	DIAMETER in.	pF/ft.
J81S		Twisted pair, shielded, underwater, black, Polyurethane jacket with stainless steel braid	–20 to 90	–4 to 194	0.210	28
J93		Coaxial, RG316/U, high temperature, clear, Teflon® jacket	–55 to 200	–61 to 392	0.098	29
J95		Five conductor, shielded, black, Polyurethane jacket	–20 to 90	–4 to 194	0.240	22
J96		Twisted pair, shielded, white Teflon® jacket	–80 to 150	–112 to 302	0.145	35
J9F		Twisted pair, foil shielded with drain wire, red Teflon® jacket	–70 to 200	–94 to 392	0.125	51

***Optional Covers:**

A = Armor cable covering (available with 0.190” dia. cables).

S = Stainless steel braid cable covering (available with most 0.190” dia. cables).